


PIN	SIGNL	PIN	SIGNL
1		17	VOUT
2		18	VSS
3	NC	19	VDD
4	PS	20	D7
5	C86	21	D6
6	NC	22	D5
7	V0	23	D4
8	V4	24	D3
9	V3	25	D2
10	V2	26	D1
11	V1	27	D0
12	CAP2-	28	RD
13	CAP2+	29	WR
14	CAP1+	30	A0
15	CAP1-	31	RES
16	CAP3+	32	/CS



NOTES:

1. DISPLAY TYPE: FSTN/双补偿
2. VIEWING DIRECTION: 6 0'CLOCK.
3. DRIVE METHOD: 1/64DUTY, 1/9BIAS.
4. OPERATING VOLTAGE: 9.0V.
5. POLARIZER MODE: TRANSMISSIVE/NEGATIVE.
6. OPERATING TEMP: -10°C ~ +60°C.
7. STORAGE TEMP: -20°C ~ 70°C
8. CONNECTOR: COG/NT7534
9. ALL WITHTOUT TOLERANCES. X±0.2

G10den View Display

TEL: 239-332-8868

FAX: 239-590-6066

MODEL NO

GVLCM12864G

DRAWN BY: LINSHENG

SCALE: 1:1

UNIT: MM

CHECKED BY: WQS

PAGE: 1/2

DATE: 2006.09.02

-11275E

